

# Container - MB12M

## Stackable steel container



The Goodpack MB12M is a multimodal container designed especially for use in the automotive industry.

The MB12M is a galvanized steel container, which can be stacked both empty and laden, as well as collapsed when not in use. The novel construction includes special features, such as an integrated folding lid, two removable sidewalls (one foldable) and two document pouches on the exterior. It is safe, easy and quick to both assemble and disassemble by a single individual.

The MB12M offers easy handling with 4-way forklift and 2-way pallet stacker entry. It is designed for shipping components in sea containers and trucks and bringing them to the immediate vicinity of production cells and assembly lines.

### Goodpack Stackable Steel Container

#### Product highlights:

- Maximum payload 1,000 kg (2,204 lb)
- Two removable sidewalls (one foldable)
- Integrated 2-part folding lid
- Two document pouches
- Laden six high stacking in warehouse
- 24 laden MB12M's fit in a 20 ft ISO container

#### General Goodpack container features and benefits:

- Returnable and reusable
- Rugged and robust patented design
- Safe in operation
- Easy to handle - no tools required
- Frame made of galvanized steel
- Capable of carrying a wide range of payloads
- Good protection against contamination
- Size-optimized for ISO container and trailer transport
- Equipped with RFID tag for tracking purposes
- Available globally\*

\* subject to compliance with applicable trade restrictions (e.g., embargoes)

#### Ordering information:

Product	Part number	Features
Goodpack MB12M	MB12M	

#### Technical Specifications:

Dimensions (external)	1,150 x 975 x 838 (mm, L x W x H)
Dimensions (internal)	1,100 x 922 x 703 (mm, L x W x H)
Dimensions (collapsed)	1,150 x 975 x 248 (mm, L x W x H)
Volume (internal)	713 l (188 US gallon, 25.1 ft <sup>3</sup> )
Tare weight	66 ± 2 kg (146 ± 5 lb)
Maximum payload	1,000 kg (2,204 lb)
Forklift handling	4-way forklift and 2-way pallet stacker entry
Tracking	RFID tag (chip and bar code) and 2D serial number
Special features	two removable sidewalls (one foldable), 2-part folding lid, two document pouches
Stackable in warehouse*	6 (laden)
Max. weight on lowest container	5,400 kg (11,904 lb)
Stackable in transit*	3 (laden)
Quantity in 20 ft ISO**	24 (laden)
Quantity in 20 ft HC ISO**	36 (laden)
Quantity in 40 ft ISO**	48 (laden), 216 (collapsed)
Quantity in 40 ft HC ISO**	72 (laden), 264 (collapsed)
Construction	all-welded steel frame with integrated lid and collapsible walls
Material	galvanized steel frame, Galvalume® sidewalls

\* subject to local regulations

\*\* subject to local weight and load restrictions

#### Document information:

Technical data sheet	Date of issue	Language, format
GP TDS MB12M	May03/2021	English, A4