

Stackable steel container



The Goodpack MB3 is a multimodal container intended for use in transport and storage of payloads ranging from liquids and pastes to bales and solid parts.

The MB3 is a galvanized steel container, which can be stacked both empty and laden, as well as nested when empty. The construction ensures efficient protection against shocks, rough handling and contamination. The MB3 is safe, easy and quick to prepare for use and operate by a single individual.

The MB3 offers easy handling with 4-way forklift entry and a rugged build. It is used extensively for shipping foodstuffs and chemicals in sea containers and trucks.

Goodpack Stackable Steel Container

Product highlights:

- Maximum payload 1,550 kg (3,417 lb)
- Laden four high stacking in warehouse
- 16 laden MB3's fit in a 20 ft ISO container

General Goodpack container features and benefits:

- Returnable and reusable
- Rugged and robust patented design
- Safe in operation
- Easy to handle - no tools required
- Frame made of galvanized steel
- Capable of carrying a wide range of payloads
- Good protection against contamination
- Size-optimized for ISO container transport
- Equipped with RFID tag for tracking purposes
- Available globally*

* subject to compliance with applicable trade restrictions (e.g., embargoes)

Ordering information:

Product	Part number	Features
Goodpack MB3	MB3	

Technical Specifications:

Dimensions (external)	top: 1,446 × 1,135 × 1,115 (mm, L × W × H) bottom: 1,286 × 995 (mm, L × W)
Dimensions (internal)	top: 1,376 × 1,085 × 1,029 (mm, L × W × H) bottom: 1,280 × 989 (mm, L × W)
Volume (internal)	1.40 m ³ (369 US gallon, 49.4 ft ³)
Tare weight	124 ± 4 kg (273 ± 9 lb)
Maximum payload	1,550 kg (3,417 lb)
Forklift handling	4-way entry
Tracking	RFID tag (chip and bar code) and 2D serial number
Special features	stacking flaps for stacking
Stackable in warehouse*	4 (laden)
Max. weight on lowest container	5,100 kg (11,243 lb)
Stackable in transit*	2 (laden)
Quantity in 20 ft ISO**	16 (laden), 80 (empty and nested)
Quantity in 40 ft ISO**	32 (laden), 160 (empty and nested)
Quantity in 40 ft HC ISO**	32 (laden), 192 (empty and nested)
Construction	rigid all-welded frame with hinged sidewalls
Material	galvanized steel frame, Galvalume [®] sidewalls

* subject to local regulations

** subject to local weight and load restrictions

Document information:

Technical data sheet	Date of issue	Language, format
GP TDS MB3	May02/2021	English, A4